

PROMIN TRUCK 15W40 API CG-4 CF-4/SJ ACEA E2

REV.1 OF Mar /2017

LEVELS OF QUALITY

The lubricant PROMIN TRUCK 15W40 API CG-4 CF-4/SJ ACEA E2 complies with the following international specifications:

ACEA E2 · API CG-4/CF-4 SJ · MB 228.1 · MAN M271 · MIL-PRF-2104H · VOLVO VDS · CAT ECF-1-A · MACK EO-M · CUMMINS CES 20076/20071

PRODUCT DESCRIPTION

DASÖL PROMIN TRUCK 15W40 API CG-4 CF-4/SJ ACEA E2 is a 'HPDO' multigrade oil of multifunctional type formulated for naturally aspirated or supercharged diesel engines of lorries, buses and earthmoving machines even in heavy duty applications. Furthermore it can be used in diesel and petrol engines of cars and commercial vehicles. The high viscosity index allows its use under any climatic conditions, providing the maximum protection for the engine both at cold starts and at high temperatures, ensuring in this way the right viscosity even for long distances.

APPLICATIONS

DASÖL PROMIN TRUCK 15W40 API CG-4 CF-4/SJ ACEA E2 offers a high detergent and dispersant power, an excellent resistance to corrosion and oxidation and a high antifoam power. The following benefits can be obtained, if you use this product:

- a higher engine cleaning,
- a better protection against piston ring sticking,
- a reduced bore polishing (exhaust pipe polishing),
- more protection against wear. It is recommended to observe always the oil change interval as suggested by the car manufacturer.

TYPICAL FEATURES*

SAE Scale		15W40
Density at 15°C.Kg./dm ³	ASTM D1298	0.880
Viscosity at 100°C.cSt	ASTM D445	13.40
Viscosity Index	ASTM D2270	135
Flammability V.A.°C	ASTM D92	220
Pour Point °C	ASTM D97	-25
TBN mgKOH/g	ASTM D 2896	11

*The above mentioned values are indicative of production average values and are not an integral part of the specification.