

DSG/DCT Oil

REV.1 OF Mar /2017

LEVELS OF QUALITY

The lubricant DSG/DCT Oil complies with the following levels of quality:

API GL-4 · ZF TE-ML-11 · VW / AUDI (VAG)
 G 052 178, G 052 182, G 052 512, G 052 513,
 G 052 529, G 052 726, G 052 796, G 052 171,
 G 055 532, TL 52 182, G-060-162 · FORD
 WSS-M2C936-A, WSS-M2C-200-D2 · PSA ·
 MITSUBISHI · RENAULT · NISSAN · BMW
 8322 2152426 · JAGUAR 02JDE 26444 ·
 LAND ROVER LR023288 · CHRYSLER
 68157995AA · FIAT 9.55550-AV5/9.55550-
 MZ6 · MB 236.25-236.21

PRODUCT DESCRIPTION

DASÖL DSG Oil is a fully synthetic automatic transmission fluid (ATF) of excellent quality and long-standing, specially formulated to be used in next-generation DSG automatic transmissions with dual clutch transmission.

DASÖL DSG/DCT Oil has been specifically formulated for next-generation transmissions High Tech DSG used in a wide range of models VAG and in an increasing number of models made by other manufacturers.

APPLICATIONS

DASÖL DSG Oil It ensures excellent performances in terms of:

- frictional properties;
- thermal-oxidative stability;
- wear and corrosion resistance.
- foaming resistance;
- compatibility with components for automatic transmissions, elastomer seals and plastic parts.
- extending oil change intervals more fuel efficient.

TYPICAL FEATURES*

Colour		Green
Density at 15°C.Kg./dm ³	ASTM D1298	0.840
Viscosity at 100°C.cSt	ASTM D445	7.0
Viscosity Index	ASTM D2270	165
Flammability V.A.°C	ASTM D92	200
Pour Point °C	ASTM D97	-39

*The above mentioned values are indicative of production average values and are not an integral part of the specification.