

OUTBOARD 2T

REV.1 OF Mar /2017

LEVELS OF QUALITY

The lubricant DASÖL OUTBOARD 2T complies with the following international specifications:

NMMA TCW-III

PRODUCT DESCRIPTION

A special pre-diluted and ashless oil of the latest formulation for two-stroke outboard engines which complies with the NMMA TC-W3 specification, thus providing an excellent lubricating power and protection against piston ring sticking and sizing. As this is a pre-diluted product it ensures an instant homogeneous blend even at low environmental temperatures.

APPLICATIONS

Its specific formulation ensures a perfect lubricant dispersion inside lead-free petrol engines, by improving the combustion and the efficiency of the engine.

The following benefits can be obtained, if you use this product:

- reduction in smoke coming from the exhaust pipe;
- a higher engine cleaning.

It ensures the highest performance of blends: 100:4(4%). However, follow the Manufacturer's indications.

TYPICAL FEATURES*

Density at 15°C.Kg./dm3	ASTM D1298	0.870
Viscosity at 100°C.cSt	ASTM D445	8.0
Colour	Visual	Blue
Flammability V.A.°C	ASTM D92	200
Pour Point °C	ASTM D97	-18

*The above mentioned values are indicative of production average values and are not an integral part of the specification.