

# ATF DEXRON III

## LEVELS OF QUALITY

The lubricant ATF DEXRON III complies with the following international specifications:

GM DEXRON III-IIIIG · MB 236.5 - 236.9 · VOITH G607 · ALLISON C-4 · CAT TO-2 · ZF TE - ML02F, 03D, 04D, 09B, 11B, 14A, 17C · FORD MERCON V

## PRODUCT DESCRIPTION

DASÖL ATF DEXRON III is a fluid produced using carefully selected and balanced components and recommended for automatic transmissions, power steering, hydraulically assisted steering and torque convertors, whenever it is required a product able to satisfy the requirements of GENERAL MOTORS Dexron III.

It is also used as an hydraulic oil over a large temperature range for applications in the automotive, industry and marine field.

## APPLICATIONS

- It ensures excellent performances in terms of:
- frictional properties;
  - thermal-oxidative stability;
  - wear and corrosion resistance;
  - foaming resistance;
  - compatibility with components for automatic transmissions, elastomer seals and plastic parts;
  - extending oil change intervals;
  - fuel economy

Thanks to the above mentioned features and to a high viscosity index it also ensures an excellent cold fluidity, by maintaining the desired viscosity at high temperatures.

## TYPICAL FEATURES\*

Colour		Red
Density at 15°C.Kg./dm3	ASTM D1298	0.860
Viscosity at 100°C.cSt	ASTM D445	7.5
Viscosity Index	ASTM D2270	150
Flammability V.A.°C	ASTM D92	195
Pour Point °C	ASTM D97	-30

\*The above mentioned values are indicative of production average values and are not an integral part of the specification.