

PROMAX ULTRA 5W40 C3 API SN/CF ACEA C3 12

REV.1 OF Mar /2017

LEVELS OF QUALITY

The lubricant PROMAX ULTRA 5W40 C3 complies with the following international specifications:

API SN SM/CF · ACEA C3-12 · MB Approvals 229.51-229.31 · BMW LONG LIFE 04 · FORD WSS-M2C917A · VW 502.00-505.00-505.01 · PORSCHE A40 · GM DEXOS 02 · FIAT 9.55535.S2 · RENAULT RN0700-RN0710

PRODUCT DESCRIPTION

DASÖL PROMAX ULTRA 5W40 C3 is a 100% synthetic lubricant with low ash content (Low SAPS) produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO IV and EURO V emission regulations.

The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

Furthermore DASÖL PROMAX ULTRA 5W40 C3 has been specifically designed to satisfy the latest ACEA C3 specifications with a low ash content and is recommended for engines equipped with particulate filtration systems, maintenance-free and without fuel additives

TYPICAL FEATURES*

SAE Scale		5W40
Density at 15°C.Kg./dm3	ASTM D1298	0.850
Viscosity at 100°C.cSt	ASTM D445	13.2
Viscosity Index	ASTM D2270	155
Flammability V.A.°C	ASTM D92	218
Pour Point °C	ASTM D97	-33
S.A.	ASTM D874	0.79
T.B.N.	ASTM D2896	7.4

*The above mentioned values are indicative of production average values and are not an integral part of the specification.