

PROMIN TRUCK SUPER 15W40 API CI-4 CH-4

REV.1 OF Mar /2017

LEVELS OF QUALITY

The lubricant PROMIN TRUCK SUPER 15W40 API CI-4 CH-4 complies with the following international specifications:

ACEA E3-E7 A3-B4 • API CI-4/CH-4 SL • MB 228.3 MAN M3275 • VOLVO VDS-2/3 • MTU TYPE3 • RENAULT RVI RLD-2 • CAT ECF-2 • MACK EO-M PLUS • CUMMINS CES 20078 / 20077 / 20076 / 20072 / 20071 • MIL-PRF-2104H

PRODUCT DESCRIPTION

DASÖL PROMIN TRUCK SUPER 15W40 API CI-4 CH-4 is a multigrade oil of multifunctional type especially recommended for all types of low emission diesel engines, ranging from the heavy drive, the earthmoving, high speed diesel and marine engines. The quality of basic oils along with a reliable additive package guarantee an excellent behaviour in service with any types of diesel fuel and extended oil change intervals according to the information provided by Manufacturers.

APPLICATIONS

DASÖL PROMIN TRUCK SUPER 15W40 API CI-4 CH-4 can be defined as a multifunctional product to be used in all types of fleet on high speed diesel engines, in earthmoving equipment and in all supercharged DIESEL marine engines. The following benefits can be obtained, if you use this product:

- a higher engine cleaning,
- a better protection against piston ring sticking,
- a reduced bore polishing (exhaust pipe polishing),
- more protection against wear;
- extending oil change intervals.

TYPICAL FEATURES*

SAE Scale		15W40
Density at 15°C.Kg./dm3	ASTM D1298	0.880
Viscosity at 100°C.cSt	ASTM D445	13.7
Viscosity Index	ASTM D2270	140
Flammability V.A.°C	ASTM D92	218
Pour Point °C	ASTM D97	-27
TBN mgKOH/g	ASTM D 2896	9

*The above mentioned values are indicative of production average values and are not an integral part of the specification.