

PROMIX 10W40 API SJ/CF ACEA A3B3

REV.1 OF Mar /2017

LEVELS OF QUALITY

The lubricant PROMIX 10W40 API SJ/CF ACEA A3B3 complies with the following international specifications:

API SJ/CF · ACEA A3-B3 · VW 500.00 / 501.01 / 505.00 · MB 229.1

PRODUCT DESCRIPTION

DASÖL PROMIX 10W40 API SJ/CF ACEA A3B3 is a semi-synthetic multigrade lubricant produced by using high-quality components. It has been developed for modern concept petrol and diesel engines with high performance and extended replacement intervals.

It offers a high detergent and dispersant power, an excellent resistance to corrosion and oxidation and a high antifoam power.

The high viscosity index allows use under any climatic conditions (low and high external temperatures).

It provides the maximum protection for engines and guarantees the right viscosity under any operating conditions (cold starts, long distances, etc.).

It is recommended to always observe the oil change interval as suggested by the car manufacturer.

TYPICAL FEATURES*

SAE Scale		10W40
Density at 15°C.Kg./dm ³	ASTM D1298	0.870
Viscosity at 100°C.cSt	ASTM D445	13.2
Viscosity Index	ASTM D2270	140
Flammability V.A.°C	ASTM D92	210
Pour Point °C	ASTM D97	-27
T.B.N.	ASTM D2896	7

*The above mentioned values are indicative of production average values and are not an integral part of the specification.