

PROMIX 5W30 API SL/CF ACEA A5B5 A1B1

REV.1 OF Mar /2017

LEVELS OF QUALITY

The lubricant PROMIX 5W30 API SL/CF ACEA A5/B5 A1/B1 complies with the following international specifications:

API SL/CF · ACEA A5/B5 A1/B1 · FORD WSS M2C-913C

PRODUCT DESCRIPTION

DASÖL PROMIX 5W30 API SL/CF ACEA A5B5 A1B1 is a synthetic multigrade lubricant with the specific Fuel Economy formula which has been produced to reach the highest performance and reliability standards in modern concept petrol and diesel engines. It offers a high detergent and dispersant power, an excellent resistance to corrosion and oxidation and a high antifoam power.

The high viscosity index allows use under any climatic conditions (low and high external temperatures).

It provides the maximum protection for engines and guarantees the right viscosity under any operating conditions (cold starts, long distances, etc.).

It is recommended to always observe the oil change interval as suggested by the car manufacturer.

TYPICAL FEATURES*

SAE Scale		5W30
Density at 15°C.Kg./dm3	ASTM D1298	0.850
Viscosity at 100°C.cSt	ASTM D445	11
Viscosity Index	ASTM D2270	145
Flammability V.A.°C	ASTM D92	200
Pour Point °C	ASTM D97	-30
T.B.N.	ASTM D2896	8

*The above mentioned values are indicative of production average values and are not an integral part of the specification.